

In the claims:

1. (currently amended) A method for producing a magnetically excitable core (24) having a core winding (40) for an electrical machine, by which in a method step (S1), the core (24), having a substantially parallelepiped shape (20) with slots (32) extending parallel on one side, is furnished, into whose slots (32), in a method step (S2), the core winding (40) is inserted by winding sides (36), and then in a method step (S3), the core (24) together with the core winding (40) is reshaped into a cylindrical ring shape with radially inward-oriented slots (32), characterized in that in each case all the winding sides (36) that are inserted into each slot (32) are pressed together into a slot shape (119) in a tool (44) and together plastically reshaped before being inserted into the slot (32) to permanently assume the slot shape (119).

2. (Previously presented) The method of claim 1, characterized in that the core (22) is fabricated in such a way that on each of core ends (61) to be joined together, there is one half-tooth (88) each in the circumferential direction.

3. (Previously presented) The method of claim 1,

characterized in that the winding sides (36) of the core winding (40) are pressed into the slot shape (119), which corresponds to a cross-sectional shape of the slots (32) of the core (24).

4. (Previously presented) A method for producing a magnetically excitable core (24) having a core winding (40) for an electrical machine, by which in a method step (S1), the core (24), having a substantially parallelepiped shape (20) with slots (32) extending parallel on one side, is furnished, into whose slots (32), in a method step (S2), the core winding (40) is inserted by winding sides (36), and then in a method step (S3), the core (24) together with the core winding (40) is reshaped into a cylindrical ring shape with radially inward-oriented slots (32), wherein in each case all the winding sides (36) that are inserted into each slot (32) are pressed into a slot shape (119) in a tool (44) and reshaped before being inserted into the slot (32), characterized in that the winding sides (36) of the core winding (40) are pressed into the slot shape (119), which corresponds to a cross-sectional shape of the slots (32) of the core (24), minus at least a fraction of a thickness (d_{iso}) of an insulating layer (123).

5. (Previously presented) A method for producing a magnetically excitable core (24) having a core winding (40) for an

electrical machine, by which in a method step (S1), the core (24), having a substantially parallelepiped shape (20) with slots (32) extending parallel on one side, is furnished, into whose slots (32), in a method step (S2), the core winding (40) is inserted by winding sides (36), and then in a method step (S3), the core (24) together with the core winding (40) is reshaped into a cylindrical ring shape with radially inward-oriented slots (32), wherein in each case all the winding sides (36) that are inserted into each slot (32) are pressed into a slot shape (119) in a tool (44) and reshaped before being inserted into the slot (32), characterized in that the core winding (40) is wound with at least one winding overhang (115).

6. (Previously presented) The method of claim 5, characterized in that a spacing (d2) of one winding side (36) from an adjacent, winding side (36) is wound larger than a spacing (d1) between two slots (32).

7. (Original) The method of claim 6, characterized in that by the pressing of the winding sides (36) into the slot shape (119), the at least one overhanging winding side (36) is permanently lifted out of a plane formed by the non-overhanging winding sides (36).

8. (Previously presented) A method for producing a magnetically excitable core (24) having a core winding (40) for an

electrical machine, by which in a method step (S1), the core (24), having a substantially parallelepiped shape (20) with slots (32) extending parallel on one side, is furnished, into whose slots (32), in a method step (S2), the core winding (40) is inserted by winding sides (36), and then in a method step (S3), the core (24) together with the core winding (40) is reshaped into a cylindrical ring shape with radially inward-oriented slots (32), wherein in each case all the winding sides (36) that are inserted into each slot (32) are pressed into a slot shape (119) in a tool (44) and reshaped before being inserted into the slot (32), characterized in that the core winding (40) is embodied as a two-layer loop winding.

9. (Previously presented) A method for producing a magnetically excitable core (24) having a core winding (40) for an electrical machine, by which in a method step (S1), the core (24), having a substantially parallelepiped shape (20) with slots (32) extending parallel on one side, is furnished, into whose slots (32), in a method step (S2), the core winding (40) is inserted by winding sides (36), and then in a method step (S3), the core (24) together with the core winding (40) is reshaped into a cylindrical ring shape with radially inward-oriented slots (32), wherein in each case all the winding sides (36) that are inserted into each slot (32) are pressed into a slot shape (119) in a tool (44) and reshaped before being inserted into the slot (32), characterized in that the core (24),

before the core winding (40) is inserted into the slots (32), is bent over a core spine (89) in such a way that slot openings (72) for insertion of the winding sides (36) are widened.

10. (Withdrawn) The method of claim 1, characterized in that the core winding (40) is embodied as a simple, single-layer loop winding.

11. (Previously presented) A method for producing a magnetically excitable core (24) having a core winding (40) for an electrical machine, by which in a method step (S1), the core (24), having a substantially parallelepiped shape (20) with slots (32) extending parallel on one side, is furnished, into whose slots (32), in a method step (S2), the core winding (40) is inserted by winding sides (36), and then in a method step (S3), the core (24) together with the core winding (40) is reshaped into a cylindrical ring shape with radially inward-oriented slots (32), wherein in each case all the winding sides (36) that are inserted into each slot (32) are pressed into a slot shape (119) in a tool (44) and reshaped before being inserted into the slot (32), characterized in that the winding overhang (115) is inserted into the at least one slot (32) before a conclusion of a bending of the core (24) into the cylindrical ring shape (52).

Claims 12-19 cancelled.

20. (Withdrawn) A method for producing a magnetically excitable core (24) having a core winding (40) for an electrical machine, by which in a method step (S1), the core (24), having a substantially parallelepiped shape (20) with slots (32) extending parallel on one side, is furnished, into whose slots (32), in a method step (S2), the core winding (40) is inserted by its winding sides (36), and then in a method step (S3), the core (24) together with the core winding (40) is reshaped into a cylindrical ring shape (52) with radially inward-oriented slots (32), characterized in that the core winding (40) is wound with at least one winding overhang (15), and at least one winding overhang (115) has an overhanging winding side (36), which before an insertion of the winding in the slots (32) is lifted from a plane formed by non-overhanging winding sides (36).

21. (currently amended) A method for producing a magnetically excitable core (24) having a core winding (40) for an electrical machine, by which in a method step (S1), the core (24), having a substantially parallelepiped shape (20) with slots (32) extending parallel on one side, is furnished, into whose slots (32), in a method step (S2), the

core winding (40) is inserted by winding sides (36), and then in a method step (S3), the core (24) together with the core winding (40) is reshaped into a cylindrical ring shape with radially inward-oriented slots (32), characterized in that in each case all the winding sides (36) that are inserted into each slot (32) are pressed together into a slot shape (119) in a tool (44) and together plastically reshaped before being inserted into the slot (32) to permanently assume the slot shape (119), which corresponds to a shape of each slot (32).

22. (previously presented) A method for producing a magnetically excitable core (24) having a core winding (40) for an electrical machine, with each core winding (40) having core winding sides (36), and each core winding side (36) having a cross section, by which in a method step (S1), the core (24), having a substantially parallelepiped shape (20) with slots (32) extending parallel on one side, is furnished, into whose slots (32), in a method step (S2), the core winding (40) is inserted by its winding sides (36), and then in a method step (S3), the core (24) together with the core winding (40) is reshaped into a cylindrical ring shape with radially inward-oriented slots (32), characterized in that in each case the cross sections of all the winding sides (36) that are inserted into each slot (32) are pressed into a slot shape (119) in a tool (44) and plastically reshaped before being inserted into the slot (32) to permanently

assume the slot shape (119).